

// isolated RS485/RS422 - Ethernet
MODBUS TCP - MODBU



PRICE

| | |
|----------|-------|
| dealer | 104 € |
| end user | 119 € |

Technical data

| | |
|-------------------------------|---|
| ethernet module | K3 USR |
| protocol | TCP, IP, UDP, ARP, ICMP, DNS, DHCP, HTTP, Web socket, HTTPD client |
| network interface - auto de | 10/100 Base-T Ethernet, MDI/MDIX |
| serial port | RS485 - half duplex, RS422 - full duplex |
| transmitter control | |
| Tx enable | |
| receiver control | |
| TxD, permanent | |
| transferred signals | TxD, RxD |
| serial data bits | 5, 6, 7, 8 |
| stop bit | 1, 2 |
| check bits | None, Even, Odd, Space, Mark |
| serial flow control | None, XON/XOFF, CTS/RTS |
| conntransfer rate | 600b/s - 512kb/s |
| setting | internal web server, PC built-in SW, serial command |
| RS422/RS485 isolation | 2,5 kV |
| connector RS485/RS422 | D - SUB 9 pin M |
| connector Ethernet | RJ45 |
| connector power supply | plug 1,3mm |
| power supply | 5 - 32V DC |
| overvoltage (soft) protection | 6000V over 1000ms |
| optical indication | power, RxD, TxD, Tx enable, link activity, half duplex, full duplex |
| input supply | max. 2 W |
| dimension | 95 x 35 x 50 mm |

[user's manual](#)