

// **RS232, isolated RS485/RS422 - Ethernet  
MODBUS TCP - MODBUS**



**PRICE**

dealer	109 €
end user	129 €

---

**Technical data**

ethernet module	K7 USR
protocol	TCP, IP, UDP, ARP, ICMP, DNS, DHCP, HTTP, Web socket, HTTPD client
network interface - auto detect	10/100 Base-T Ethernet, MDI/MDIX
serial port	RS232 - full duplex, RS485 - half duplex, RS422 - full duplex
transmitter control	
TxD, permanent (RS422)	
receiver control	
inverse to TxD, permanent	
transferred signals	TxD, RxD
serial data bits	5, 6, 7, 8
stop bit	1, 2
check bits	None, Even, Odd, Space, Mark
serial flow control	None, XON/XOFF, CTS/RTS
transfer rate RS232	
600b/s - 115kb/s	
transfer rate RS422/RS485	500b/s - 1Mb/s
setting	internal web server, PC built-in SW, serial command
RS422/RS485 isolation	2,5 kV
power supply	5 - 32V DC
overvoltage (soft) protection	600W or 100W
optical indication	power, RxD, TxD, link activity
input supply	max. 2 W
dimension	90 x 58 x 52 mm

---

[user's manual](#)