

// **isolated RS485/RS422 - Ethernet  
MODBUS TCP - MODBUS**



PRICE

dealer	109 €
end user	129 €

---

**Technical data**

ethernet module	K3 USR
protocol	TCP, IP, UDP, ARP, ICMP, DNS, DHCP, HTTP, Web socket, HTTPD client
network interface - auto detect	10/100 Base-T Ethernet, MDI/MDIX
serial port	RS485 - half duplex, RS422 - full duplex
transmitter control	
Tx enable	
receiver control	
TxD, permanent	
transferred signals	TxD, RxD
serial data bits	5, 6, 7, 8
stop bit	1, 2
check bits	None, Even, Odd, Space, Mark
serial flow control	None, XON/XOFF, CTS/RTS
connetransfer rate	600b/s - 512kb/s
setting	internal web server, PC built-in SW, serial command
RS422/RS485 isolation	2,5 kV
connector RS485/RS422	D - SUB 9 pin M
connector Ethernet	RJ45
connector power supply	plug 1,3mm
power supply	5 - 32V DC
overvoltage (soft) protection	600W or 1000W
optical indication	power, RxD, TxD, Tx enable, link activity, half duplex, full duplex
input supply	max. 2 W
dimension	95 x 35 x 50 mm

---

[user's manual](#)