

//

oddelený RS485/RS422 - Ethernet MODBUS TCP - MODBUS RTU



CENA

dealer	109 €
end user	129 €

Technické údaje

ethernet modul	K7 USR
protokol	TCP, IP, UDP, ARP, ICMP, DNS, DHCP, HTTP, Web socket, HTTPD client
network interface - auto detect	10/100 Base-T Ethernet, MDI/MDIX
serial port	RS485 - half duplex, RS422 - full duplex
riadenie vysieláča	
Tx enable	
riadenie prijímača	
TxD, permanent	
prenášané signály	TxD, RxD
dátové bity	
5, 6, 7, 8	
stop bity	1, 2
parita	
None, Even, Odd, Space, Mark	
riadenie toku	
None, XON/XOFF, CTS/RTS	
prenosová rýchlosť	
600b/s - 512kb/s	
nastavenie	
internal web server, PC built-in SW, serial command	

RS422/RS485 oddelenie	2,5 kV
konektor RS485/RS422	D - SUB 9 pin M
konektor Ethernet	RJ45
konektor napájanie	plug 1,3mm
napájanie	5 - 32V DC
prepäťová (soft) ochrana	600W 10/1000us
optická indikácia	power, RxD, TxD, Tx enable, link activity, half duplex, full duplex
príkon	
max. 2 W	
rozmery	95 x 35 x 50 mm

[užívateľský manuál](#)